




Copper Ground Wire

Ordering information

To create a part number, use the following guide. Standard products are indicated in bold type.

Basic Product	Add Plating	Add Insulation	Add Length in Feet
EM 0140 (solid #14 AWG)	T - tinned B - bare	N - none B - black SL - slate* G - green	XX
EM 1200 (solid #12 AWG) 	T - tinned B - bare	N - none B - black SL - slate G - green	XX
EM 3226 (solid #10 AWG) 	T - tinned B - bare	N - none B - black SL - slate G - green	XX
EM 3227 (solid #8 AWG)	B - bare	N - none B - black SL - slate G - green	XX
EM 3225 (solid #6 AWG) 	T - tinned B - bare	N - none B - black SL - slate G - green	XX
EM 4500 (solid #6 AWG waterproof)	B - bare	B - black G - green	XX
EM 4560 (solid #6 AWG with .120 thick PVC insulation)	T - tinned B - bare	B - black G - green SL - slate	XX
EM 3400 (#6 AWG 7-strand)	T - tinned B - bare	N - none B - black SL - slate G - green	XX
EM 4000 (solid #4 AWG)	T - tinned B - bare	N - none B - black SL - slate G - green	XX
EM 2223 (solid #2 AWG)	T - tinned B - bare	N - none B - black SL - slate G - green	XX

*formerly GR - gray

Copper ground wire is available from Electric Motion in bare, tinned, insulated, and waterproof versions of various lengths. These are generally available in #12, #10, #8, #6, #4, or #2 AWG, hand coiled or on a spool.




Loose Piece Crimp Terminals

Ordering information

EM 6-10-R
#6 AWG Tin-Plated Copper Ring
#10 mounting hole.


Standard packaging: 100/sm bx, 1000/lg bx, 1.5 lb/sm bx, 13 lb/lg bx.

No minimum order.



EM 6-25-R
#6 AWG Tin-Plated Copper Ring
1/4" mounting hole.

Standard packaging: 100/sm bx, 1000/lg bx, 1.5 lb/sm bx, 13 lb/lg bx. No minimum order.



EM 14-TF
#14 AWG TERMI-FOIL®

Standard packaging: 100/bg, 1000/bx, 1.16 lb/bg. No minimum order.

EM 10-TF
#10 and #12 AWG TERMI-FOIL®

Standard packaging: 100/bg, 1000/bx. No minimum order.

See crimp tool on page 27.